

Sounder

FI700/WM/SOUR



- **ADM loop technology with Labor Strauss/700 protocol**
- **Can be activated with three different tone types**
- **Sound level adjustable**
- **Optionally with protection class IP66**
- **Low power consumption**
- **Integrated dual-isolator**



Description

The red Loop Sounder **FI700/WM/SOUR** is powered and actuated via the ADM loop with Labor Strauss/700 protocol. The sounder can be activated by the fire detection control panel with one of the following three tone types, depending on the parameter setup and the system condition:

- Alternating tone 990Hz/650Hz,
- Continuous tone 990Hz, or
- Pulsed tone 990Hz.

If several sounders are activated at the same time, they are synchronised by the control panel, in order to generate a uniform warning tone. The sound level can be easily adjusted by means of a potentiometer. The address of the sounder is set in the range 1 to 240 by means of the Programming Unit FI750/PU. Alternatively,

the sounder can be addressed automatically if it is connected to a compatible fire detection control panel.

An integrated dual-isolator disconnects the loop in case of a short circuit. In this way, the undisturbed communication with the loop elements outside the faulty loop section is ensured.

The robust plastic case is equipped with a deep mounting base and is designed for indoor wall mounting.

The Loop Sounder **FI700/WM66/SOUR** is suitable for harsh environmental conditions, thanks to its dust and water protected design with protection class IP66.

Specifications

Operating voltage	Supply through loop voltage
Current consumption from loop	typ. 70µA (sounder off) max. 7mA (sounder on)
Sound level	100dB(A) at 1m distance
Tone type 1	alternating tone (990Hz for 0.25s/650Hz for 0.25s)
Tone type 2	continuous tone 990Hz
Tone type 3	pulsed tone 990Hz (0.5s on, 0.5s off)
Ambient temperature	-10°C to +55°C
Colour	red




0832-CPD-1064

Building Safety. Building Security.

LST

Loop Sounder	
Protection class	IP21
Dimensions W x H x D	108 x 108 x 95 (mm)
Weight	255g
Approval	0832-CPD-1064
Order number	355180
Order name	Sounder/700ISM/Red FI700/WM/SOUR

Loop Sounder IP66	
Protection class	IP66
Dimensions W x H x D	110 x 110 x 105 (mm)
Weight	300g
Order number	355189
Order name	Sounder/IP66/700ISM/Red FI700/WM66/SOUR



Building Safety. Building Security.

