



Alarm Control Panel+Remote Keypad

Specifications

Function	Model	FC-7668
External AC Power supply		185~230V AC
Output		13V AC/3A
Backup power supply Duration		16 hours
Backup Battery		12V/7 Ah, (rechargeable lithium battery)
The method of alarming dial		Telephone alarm and GSM alarm
DTMF dial frequency variation		<1.5%
Communication protocol with CMS		Ademco contact ID
Frequency		433/868MHz
Signal transmit distance		100 to 120 meters(open area)
Operation temperature		0°C-45°C (32F-120F)
Storage temperature range		-20°C-60°C (-4F-140F)
Relative humidity		85% at 30 °C (86F)

Features | MODEL:FC-7668

- Zones: 8 wired+32 wireless + 128 bus zones
- Keypad and remote: support 10pcs LCD keypad and 16 remotes
- Password: 1 installer code, 1 master user code, 32 user codes
- CMS: 2 CMS follow me numbers, 2 account number
- Voice number: 8 voice numbers, Voice prompting operation
- Event log: 152 event logs review
- Partition: 8 partitions, user can assign any zones to any one or several partitions. User can authorize any keypad to manage each partition and several partition. User can set different voice number to be notified when any of the partition is triggered.
- Auto armed/ disarmed: 8 timer for auto arm/disarm, user can set timer for different partitions.
- Siren and electric switch: support 8 wireless two way siren, 32 wireless electric switch.
- Module expanded: GSM/GPRS module, series port module, relay module, TCT/IP module PGM output, SD card port. User can upgrade the system to latest software via SD card in local and also can import the zone names for SD card.