



Alarm Control Panel+Remote Keypad

Specifications

| Function | Model | ST-IIIB |
|---------------------------------|-------|------------------------------------------|
| External AC Power supply | | 185~230V AC |
| Output | | 13V AC/3A |
| Backup power supply Duration | | 16 hours |
| Backup Battery | | 12V/7 Ah, (rechargeable lithium battery) |
| The method of alarming dial | | Telephone alarm and GSM alarm |
| DTMF dial frequency variation | | <1.5% |
| Communication protocol with CMS | | Ademco contact ID |
| Frequency | | 433/868MHz |
| Signal transmit distance | | 100 to 120 meters(open area) |
| Operation temperature | | 0°C-45°C (32F-120F) |
| Storage temperature range | | -20°C-60°C (-4F-140F) |
| Relative humidity | | 85% at 30 °C (86F) |

Features | MODEL:ST-IIIB

- Touch panel, LCD display screen;
- Voice indication for all operation steps;
- 8 wired+ 32 wireless zones;
- Support landline and SIM card;
- Supports to send call or SMS message to the phone;
- 4 phone numbers can be set/2CMS number;
- Support remote control via phone/voice alarm and intercom function;
- Support Android/Iphone APP;
- 120 alarm log and inquiry / 10 seconds for recording;
- Inspections wireless device lose or low battery;
- Built -in rechargeable battery back up to provides continues operation;
- Built-in door bell tone;
- Built-in high tone loudspeaker.