

Multi-media Fingerprint Time Attendance and Access Control Terminal











## Introduction

IN01-A is an innovative biometric fingerprint reader for time attendance and access control applications, Built-in 2000 mAh backup battery can eliminates the trouble of power-failure. Support optional GPRS and Wi-Fi. The IN01-A features the fastest commercial-based fingerprint matching algorithm and ZK high-performance, high-image quality optical fingerprint sensor. The 3" TFT can display more information vividly, including fingerprint image quality and verification result etc. TCP/IP communication is standard and make sure the data transmission between terminal and PC can be easily done within several seconds.

## Features:

- \* Color TFT screen with GUI Interface for ease of use
- \* ZK Optical Sensor
- \* 1 touch a-second user recognition
- \* Reads Fingerprint and/or PINs
- \* Optional integrated proximity or smart card reader
- \* Built-in Serial and Ethernet ports
- \* Multi Language Support
- \* Built-in battery backup provides approx
- 4 hours continuous operation
- \* Optional built-in wireless Wi-Fi or GPRS for wireless communication
- \* Real-time 1-touch data export 3rd party hosted & non-hosted applications
- \* SDK available for OEM customers and software developers

## RS232/485 Converter RS485 HUB

IN01-A

**USB** Key

**Electric Bell** 

Serial Printer

**Exit Button** 

Configuration:

## Specifications:

| Fingerprint Capacity     | 3000 templates  |
|--------------------------|---|
| Transaction Capacity     | 100,000   |
| Hardware Platform        | ZEM510  |
| Sensor                   | ZK Optical Sensor   |
| Algorithm Version        | ZK Finger v10.0 and v9.0, default v10.0   |
| Communication            | RS232/485, TCP/IP, USB-Client, USB-Host   |
| Access Control Interface | electric lock, door sensor, exit button, alarm,   |
| for                      | door bell.  |
| Wiegand signal           | Input & Output  |
| Standard Functions       | Work code, SMS, DLST, Self-Service Query, Automatic<br>Status Switch, Back-up battery, anti-pass back |
| Optional Functions.      | ID/Mifare/HID, Extensible barcode, Relay-bell,<br>Scheduled-bell, Web-server, SOAP, 9 digit user ID,  |
|                          | Wi-Fi, GPRS   |
| Display                  | 3 inches TFT Screen   |
| Power Supply             | 12V DC 3A   |
| Operating Temperature    | 0 ℃- 45 ℃   |
| Operating Humidity       | 20% - 80%   |
| Dimension(W×H×D)         | 210×157×50 mm   |