

GT-ADD210/213/220

High Definition Analog Cameras



Features:

- OV9712/SONY225/SONY_IMX322 sensor
- 3D DNR and digital WDR
- Transmission distance up to 500 meters
- Support real-time transmission

Specifications

Model	GT-ADD210	GT-ADD213	GT-ADD220
Sensor	AHD 2431+OV9712	AHD 2431+ Sony 225	NXP2441H+SONY_IMX322
Light-sensing surface area	1/4-inch	1/2.8-inch	1/2.8-inch
Resolution	1.0MP	1.3MP	2.0MP
Definition	1280(H)x720(V)	1280(H)x960(V)	1920(H)x1080(V)
Video Frame	1280x720@25 fps;1280x720@30 fps		1920x1080@25 fps;
Frame Rate In Main Stream	1—4Mbps	1—5Mbps	8Mbps
Min. illumination	IR on: 0 Lux		
Lens	3.6mm (2.8/6.0mm optional)	3.6mm (6.0mm optional)	3.6mm (6.0mm optional)
Signal Noise Ratio	40dB	45dB	40dB
White Balance	Auto		
Shutter	Auto		
Infrared Resection	IR-CUT		
IR Distance	10m		
Power Supply	DC 12V /1.5A		
Operating Temperature	-10 °C- 50 °C		
Net/Gross Weight	0.37kg / 0.47kg		
Dimension(color box)	193mm*105mm*102mm		

